

Size : 3060 x 230 mm

TESTS & STANDARDS

Standard description	Standard code
Impact resistance	No deformation observed. (Tested at 50 LBS)
Tensile strength	>37.0 MPa
Tensile modulus	>2000 MPa
Surface distortion	None at 120F
Squareness	<1/8" of square
Length	Within 1/4" of specification
Lock control	Complies
Color Change	<2 grayscales (16 hrs under 1200W/m2 UV radiation at 50 degrees)



- ◆ No VOC emission
- ◆ Fire Retardant
- ◆ Waterproof
- ◆ Termite & Rust proof
- ◆ Anti-Bacterial
- ◆ Impact resistant

10 Years Warranty

- ◆ Maintenance Free
- ◆ Unique Interlocking
- ◆ Sleek Design
- ◆ Seamless Post Installation
- ◆ Real Wood Feel

PERFORMANCE

Reaction to fire	Prong wife at t acc complies ump it a test accure, les mammaliy rating when tested in accordance to IS 10151
Reaction to cold	Pare panels and its accessories comply with cold duration test (-20 degrees) in accordance with IS 10151.
Anti-Bacterial	Pare panels and its accessories were tested with 1000 cfu/ml of various different fungi and bacteria;within 30 seconds, the value is reduced to 0 cfu/ml thus making it a truly anti-bacterial product.
Relevant codes and regulations compliance	Conforms to ASTM Specifications D-4477 Color: Uniformity is spectrophotometrically controlled. Gloss: Uniformity is controlled with a 75 degrees glossmeter Lock: Optically measured and controlled.

Ideal for

- Residential Buildings
- Commercial Properties
- Hotels
- Business Hubs
- Offices
- Club houses & Cafes

Uses

Wall & Ceilings

WhatsApp +971 54 569 1963

Facebook danubebuildingmaterial

Twitter danubebuildingmaterial

LinkedIn danubebuildingmaterial

Instagram danubebuildingmaterials

Danube Building Materials FZCO

P.O. Box 18022, Jebel Ali Free Zone, Dubai, U.A.E. | Tel : +971 4 8871234, Fax : +971 4 8810158 | Email: enquiry@aldanube.com

www.danubebuildingmaterials.com