

Size : 2800 x 1400 x 12 mm

Origin : Netherlands and Ukraine



Physical & Technical Properties

Properties	Unit	Value
Thickness tolerance	mm	± 1
Density	g/cm ³	1043
Izod Impact Strength (notched)	kJ/m ²	3.21
Modulus of Elasticity (Chord 0.05%-0.25%)	MPa	2287
Tensile Maximum Load	N	6100
Tensile Strength (yield)	MPa	17.55
Tensile Strength(break)	MPa	14.29
Elongation at Break	%	3.8
Shore D Hardness	D	72.5
Melting point	°C	210
Finish	Matte, Single-faced	
Scratch Resistance	Medium	
Stiffness	High	
Moisture Absorption	None	

- Machining
- Drilling
- Cutting
- Sanding
- Polishing
- Thermoforming
- Gluing
- Screwing

Application

- ◆ Shelves
- ◆ Stands
- ◆ Wall cladding
- ◆ Podiums
- ◆ Racks

☎ +971 54 569 1963

📘 danubebuildingmaterial

🐦 danubebuildingmaterial

🌐 danubebuildingmaterial

📷 danubebuildingmaterials

Danube Building Materials FZCO

P.O. Box 18022, Jebel Ali Free Zone, Dubai, U.A.E. | Tel : +971 4 8871234, Fax : +971 4 8810158 | Email : enquiry@aldanube.com

www.danubebuildingmaterials.com